
Subject: Shown values on mileposts

Posted by [Christian Rahmig](#) on Fri, 15 Mar 2013 22:05:22 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hello everybody,

at the last railML meeting in Berlin, we discussed about the following aspects of mileposts (de: Hektometertafeln):

- (1) Are there "switchable" mileposts?
- (2) Are there references between mileposts and mileage changes?

Number (1) can be answered with "no". For number (2) the situation is more complex (see [1]) so that a Trac ticket has been filed [2]:

It is necessary to put the offset in a separate field. Only then it is possible to distinguish between the mileage value in the gap and after the gap. In particular "123.4 +1" is a different value than "123.5". Therefore, I suggest to give the milepost two attributes: "shownValue" given in kilometers with 3 digits behind the comma and "shownOffset" given in dezi-kilometers without any digits behind the comma (e.g. 100m = 1).

Of course, it can happen, that the milepost is situated exactly at the position of a mileage change. So, I suggest to include an optional reference mileageChangeRef to the mileage change element.

Any comments appreciated...

[1] http://www.drehscheibe-foren.de/foren/read.php?3,2958137,296_0646

[2] <https://trac.assembla.com/railML/ticket/228>

Regards

--

Christian Rahmig
railML.infrastructure coordinator
