

---

Subject: [railML3] Limitation of <hasGaugeClearanceMarker> in <switchIL>  
Posted by [Georg Boasson](#) on Wed, 10 May 2023 11:10:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

The maximum number of child element <hasGaugeClearanceMarker> in <switchIL> must be extended to more than 2, which is the limitation in railML3.2. Bane NOR will use each <hasGaugeClearanceMarker> to reference one clearance point. The clearance point is defined by using a <trainDetectionElement> with type="clearancePoint". See attached file for an example of a switch with 4 clearance points.

Proposal: The limitation of <hasGaugeClearanceMarker> elements in the <switchIL> can be set to unlimited.

---

### File Attachments

1) [Example with clearance points.pdf](#), downloaded 93 times

---

---

Subject: Re: [railML3] Limitation of <hasGaugeClearanceMarker> in <switchIL>  
Posted by [Dominik Looser](#) on Fri, 09 Jun 2023 07:16:57 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

I agree that there should not be a limitation on the number of <hasGaugeClearanceMarker>.

---

---

Subject: Re: [railML3] Limitation of <hasGaugeClearanceMarker> in <switchIL>  
Posted by [Jörg von Lingen](#) on Mon, 12 Jun 2023 08:16:24 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Thanks for your input. Originally, the use of <hasGaugeClearanceMarker> was not considered in the way as suggested from BaneNOR (Georg B). But I agree the proposal is more clear and thus no limitation shall be set.

---

Dr.-Ing. Jörg von Lingen - Interlocking scheme coordinator  
railML.org (Registry of Associations: VR 5750)  
Phone Coordinator: +49 351 87759 40; railML.org: +49 351 47582911  
Altplauen 19h; 01187 Dresden; Germany [www.railml.org](http://www.railml.org)

---