
Subject: [railML3] Insulated Electrification Sections
Posted by [Dominik Looser](#) on Thu, 08 Jun 2023 07:35:37 GMT
[View Forum Message](#) <> [Reply to Message](#)

Dear community

Our customer would like to model insulated electrification sections in railML3 and we are thinking about using the existing <electrificationSection>-element and its subelements.

One type of electrification section is called "Electrification Section Insulator" (mostly used in stations) and the other one is an "Electrification Section Break" that has a length extent.

How could we - as specific as possible - model this in railML3? Our idea is to use the subelement <phaseSeparationSection> for Electrification Section Breaks.

Does anyone have input on what the <phaseSeparationSection> is meant for and how to model these types of insulated sections?

Thank you and best regards,
Dominik Looser

Subject: Re: [railML3] Insulated Electrification Sections
Posted by [Jörg von Lingen](#) on Sat, 09 Sep 2023 12:51:27 GMT
[View Forum Message](#) <> [Reply to Message](#)

Dear all,

I would use subelement <phaseSeparationSection> for modelling of Electrification Section Breaks (de: Schutzstrecke). There needs to be an <electrificationSection> defined for the overall electrified line. An additional <electrificationSection> uses child <phaseSeparationSection> with the position, length and flags, whether it is insulated (power off) or earthed. This shall look like the attached example.

Dr.-Ing. Jörg von Lingen - Interlocking scheme coordinator
railML.org (Registry of Associations: VR 5750)
Phone Coordinator: +49 351 87759 40; railML.org: +49 351 47582911
Altplauen 19h; 01187 Dresden; Germany www.railml.org

File Attachments

1) [electrification.xml](#), downloaded 69 times
