
Subject: Re: Additional commercial attributes from TAP TSI for timetables

Posted by [Stefan Jugelt](#) on Mon, 21 Sep 2015 16:02:37 GMT

[View Forum Message](#) <> [Reply to Message](#)

Dear all,

as agreed during our railml timetable meeting last week I have created for the proposed attribues one example for the coding of places and services for a train part:

Example:

```
<?xml version="1.0" encoding="UTF-8"?>
<!--Sample XML file generated by XMLSpy v2015 sp2
(http://www.altova.com)-->
<railml xmlns="http://www.railml.org/schemas/2013"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://www.railml.org/schemas/2013 railML.xsd">
<metadata>
<organizationalUnits>
  <railwayUndertaking id="CompanyCode_1080" code="1080"/>
</organizationalUnits>
</metadata>
<infrastructure id="inf-0815">
  <operationControlPoints>
    <ocp id="enee_8010085">
      <designator entry="8010085" register="ENEE"/>
    </ocp>
    <ocp id="enee_8010205">
      <designator entry="8010205" register="ENEE"/>
    </ocp>
  </operationControlPoints>
</infrastructure>
<timetable id="tt-0815">
  <trainParts>
    <trainPart id="TrainPart-0815-1">
      <formationTT>
        <passengerUsage>
          <!-- 100 seats in 1st class -->
          <places category="seatingFirstClass" count="100"/>
          <!-- 300 seats in 2nd class -->
          <places category="seatingSecondClass" count="300"/>
          <!-- Snack trolley available -->
          <service name="trolley" count="1"/>
        </passengerUsage>
      </formationTT>
      <ocpsTT>
        <ocpTT ocpRef="enee_8010085" ocpType="begin"/>
        <ocpTT ocpRef="enee_8010205" ocpType="end"/>
      </ocpsTT>
    </trainPart>
  </trainParts>
</timetable>
</railml>
```

```
</ocpsTT>
<organizationalUnitBinding>
  <railwayUndertaking ref="CompanyCode_1080"/>
</organizationalUnitBinding>
</trainPart>
</trainParts>
</timetable>
</railml>
```

Some further explanations:

1. The code values for the rail:places/@category shall be stored in an external code list, not in an enumeration in railML.
2. The code values are available in the files "Codelist_B.4.7161.xml" (servies) and "Codelist_B.4.9039.xml" (places).
3. The enumeration for the accomodation classes in "tPlaceCategory" and "tServices" are not needed anymore.

Please check the example and provide your comments.

Kind regards,

Stefan Jugelt

--
===== posted via PHP Headliner =====
