
Subject: [railML3] Time Dimension requirements from TT view
Posted by [christian.rahmig](#) on Fri, 23 Dec 2016 13:37:09 GMT
[View Forum Message](#) <> [Reply to Message](#)

Dear railML TT community,

within the ongoing development process of the new railML v3 model and schema, the topic "Time Dimension" is currently in the focus. The aim is to provide a model of time aspects that fulfills all the requirements from the different fields of application.

The timetable use cases already deal with with a lot and specific time related information and railML.org would like to integrate this long lasting knowledge into the railML3 development process, which is up to now dominated by railway infrastructure managers and their view. Therefore, I will be very happy if you provide answers and comments on the following questions:

What are the time scales that are used in railML TT use cases (seconds, minutes, days, ...)?

How are time aspects in railML TT applications usually structured?

Shall the bitmask structure be considered within the joint time dimension model?

Do you use patterns for repeating events?

How do you deal with changes in infrastructure? Which changes of infrastructure are relevant for TT? See also post from Mico Micic about topology reference data [1].

Which infrastructure changes are especially important for timetabling? E.g. Removed switches, new switches, decommissioned tracks, relocated signals etc.

What requirements do you have for the precision of infrastructure positioning?

Besides timetable periods do you require additional timestructures like project phases of construction work?

What kind of metadata (descriptive data) about the actual infrastructure data could be helpful for timetabling?

Any comments appreciated...

Thank you very much for your help and Merry Christmas everyone!

Christian

[1] <http://www.railml.org/forum/index.php?t=msg&th=476&s tart=0&>

--

Christian Rahmig
railML.infrastructure coordinator
