

---

Subject: Different ways to model tractive effort

Posted by [Laura Isenhofer](#) on Tue, 26 Feb 2019 08:40:49 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Hi,

Jernbanedirektoratet has the need to define the tractive effort of an engine in a more flexible way than it is possible right now. Our aim is to cater for all the needs that our different tools have and ideally allow for a lossless transfer from one railML-file to each of the tools.

In general, our tools seem to use 3 different approaches:

1) Discrete value table: same as railML-value table. Each pair of speed and tractive effort get one entry, values between the given value pairs need to be interpolated (linear). Accuracy is user-defined.

2) Hyperbolic curves: the curve of the tractive effort curve is defined by a hyperbola. All you need to know are the coordinates of the start and the end point of the hyperbola and with the equation  $F=P/v (+c)$  you will be able to interpolate every point on the hyperbola. Additionally to the given value pairs there's the need to specify if those points should be connected linear or hyperbolic, which can currently not be done in railML. (But could probably be done easily with a simple extension).

3) Quadratic curves: The tractive effort can also be given by the following equation:

for both the linear part as well as the curve, by giving  $b_0$ ,  $b_1$  and  $b_2$  (for different intervals). This could e.g. be implemented by using different  $z$ -values in the railML-value table to define the  $b_i$  for the different speed-intervals.

As mentioned above, we would love to find a solution that allows all 3 possibilities, so that we are able to enter the tractive effort into all of our tools we use.

Mathml does not seem to be the solution here, since it does not seem to be able to unambiguously define those equations or tables.

One of our suggestions would be to have a table with 6 columns, so that each reading system can pick the values it needs:

(speed | tractive effort | linear/hyperbolic? |  $b_0$  |  $b_1$  |  $b_2$ )

We're happy to hear other suggestions. The solution could first be a Norwegian extension and later be implemented into railML2.5.

Best regards,  
Laura

---

---

Subject: Re: Different ways to model tractive effort

Posted by [Joerg von Lingen](#) on Tue, 26 Feb 2019 09:53:43 GMT

Hi,

in our old tools we a mechanism to describe such curves per (speed) interval just marking the type and possible coefficients.

1) Polynom  $F=A+B*v+C*v^2+D*v^3$  - by choosing the coefficients A, B, C and D one can describe a wide range of different curves from just konstant to more complex ones

2) Hyperbolic  $F=A/v$  - hyperbolic curve is used for intervals with constant power (A) divided by speed

3) Quadratic  $F=(A*v1)/v^2$  - quadratic curve is used for intervals (start at v1) with field weakening from power (A)

This principles I had in mind when I presented in Nov. 2003 a possible representation in MathML - refer attachment.

Regards,  
Jörg von Lingen, Rollingstock coordinator

Laura Isenhofer wrote on 26.02.2019 09:40:

> Hi,  
>  
> Jernbanedirektoratet has the need to define the tractive  
> effort of an engine in a more flexible way than it is  
> possible right now. Our aim is to cater for all the needs  
> that our different tools have and ideally allow for a  
> lossless transfer from one railML-file to each of the tools.  
>  
>  
> In general, our tools seem to use 3 different approaches:  
>  
> 1) Discrete value table: same as railML-value table. Each  
> pair of speed and tractive effort get one entry, values  
> between the given value pairs need to be interpolated  
> (linear). Accuracy is user-defined.  
>  
> 2) Hyperbolic curves: the curve of the tractive effort curve  
> is defined by a hyperbola. All you need to know are the  
> coordinates of the start and the end point of the hyperbola  
> and with the the equasion  $F=P/v (+c)$  you will be able to  
> interpolate every point on the hyperbola. Additionally to  
> the given value pairs there's the need to specify if those  
> points should be connected linear or hyperbolic, which can  
> currently not be done in railML. (But could probably be done

> easily with a simple extension).  
>  
> 3) Quadratic curves: The tractive effort can also be given  
  
> This equation allows to precisely define the tractive effort  
> for both the linear part as well as the curve, by giving b0,  
> b1 and b2 (for different intervals). This could e.g. be  
> implemented by using different z-values in the railML-value  
> table to define the bi for the different speed-intervals.  
>  
> As mentioned above, we would love to find a solution that  
> allows all 3 possibilities, so that we are able to enter the  
> tractive effort into all of our tools we use.  
> Mathml does not seem to be the solution here, since it does  
> not seem to be able to unambiguously define those equations  
> or tables.  
>  
> One of our suggestions would be to have a table with 6  
> columns, so that each reading system can pick the values it  
> needs:  
> (speed | tractive effort | linear/hyperbolic? | b0 | b1 |  
> b2)  
>  
> We're happy to hear other suggestions. The solution could  
> first be a Norwegian extension and later be implemented into  
> railML2.5.  
>  
> Best regards,  
> Laura  
>

## File Attachments

1) [railML-MathML.pptx](#), downloaded 616 times

---

---

Subject: Re: Different ways to model tractive effort

Posted by [Thomas Nygreen JBD](#) on Tue, 05 Mar 2019 13:20:27 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Dear all,

The current railML2 valueTable could support any of the segmented functions listed by Laura and Jörg, if we for each row apply the formula

$F = \text{Sum} ( y_z * v^z )$  for all z

where each value for z is given by columnHeader@zValue.

If no column header is found and only one column is given, we would assume z = 0, meaning that F = y. This allows programs to keep listing the tractive effort for small speed steps.

This approach would support any polynomial function, such as constant (only  $z=0$ ), linear (0 and 1), quadratic (0, 1, 2) and cubic (0, 1, 2, 3), the simple hyperbolic (-1, 0) and quadratic hyperbolic (-2) listed by Laura and Jörg, and other simple rational functions where there is no shift of the  $x$  variable.

---

---

Subject: Re: Different ways to model tractive effort  
Posted by [Joerg von Lingen](#) on Wed, 01 Jul 2020 06:32:30 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Dear all,

I have transferred the issue into ticket #385 to be implemented in railML 2.5.

The suggestion is to add an alternative element "segmentTable" used instead of "valueTable". Basically this table is similar build as the known valueTable with some exceptions and a different way of interpretation.

The  $z$ Value (here "exponentValue") is of type integer and shall be taken as exponent to the  $x$ Value (here "segmentStartValue"). The latter one marks the start of an intervall or segment in the curve. The maximum  $x$ Value shall be derived from the "speed" attribute of the vehicle. The  $y$ Value (here "coefficentValue") is the value of each coefficent to be multiplied with  $x$ Value to the power of  $z$ Value. The total of all calculated values of the line gives real value need. Thus it follows the formula  $F = \text{Sum} ( y * x^z )$ .

The sample of the original data, the schema definition and the representation in railML are shown in the attached pictures.

Best regards,  
Joerg v. Lingen - Rollingstock Coordinator

#### File Attachments

---

- 1) [segmentTable03.jpg](#), downloaded 384 times
  - 2) [segmentTable02.jpg](#), downloaded 416 times
  - 3) [segmentTable01.jpg](#), downloaded 415 times
- 

---

Subject: Re: Different ways to model tractive effort  
Posted by [Thomas Nygreen](#) on Wed, 19 Aug 2020 13:48:58 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Dear all,

I think Jörg's proposal is good.

Best regards,  
Thomas Nygreen - Common schema coordinator, railML.org

---

---

Subject: Re: Different ways to model tractive effort  
Posted by [Joerg von Lingen](#) on Mon, 14 Sep 2020 07:13:02 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Dear all,

it has been implemented for railML2.5 and described in wiki  
[http://wiki2.railml.org/wiki/RS:segmentTable\\_tractiveEffort](http://wiki2.railml.org/wiki/RS:segmentTable_tractiveEffort)

--

Regards,  
Jörg von Lingen - Rollingstock Coordinator

Thomas Nygreen wrote on 05.03.2019 14:20:

- > Dear all,
  - >
  - > The current railML2 valueTable could support any of the
  - > segmented functions listed by Laura and Jörg, if we for
  - > each row apply the formula
  - >  $F = \text{Sum} ( y_z * v^z )$  for all z
  - > where each value for z is given by columnHeader@zValue.
  - >
  - > If no column header is found and only one column is given,
  - > we would assume z = 0, meaning that F = y. This allows
  - > programs to keep listing the tractive effort for small speed
  - > steps.
  - >
  - > This approach would support any polynomial function, such as
  - > constant (only z=0), linear (0 and 1), quadratic (0, 1, 2)
  - > and cubic (0, 1, 2, 3), the simple hyperbolic (-1, 0) and
  - > quadratic hyperbolic (-2) listed by Laura and Jörg, and
  - > other simple rational functions where there is no shift of
  - > the x variable.
  - >
-